

HSF RoHS Specifications

1. 材料(MATERIAL)

Housing: PA6T/PBT+30%G.F UL94V-0,Color:Black

Material : Brass

额定电流: 3 AMP

接触阻抗: 20 mΩ MAX.

绝缘阻抗: 1000 M Ω min.

耐压: AC 500V.

温度范围: -40°C to +105°C

Temperature Range: -40°C to +105°C

3P25S- 31 XX XX X XXX X 1

No. of Pins Per Row	Contact Plating	Insulator Length	Packing
3-40 ⁰	Gold/Gold Flash	OF	A: PE Bag
	G1=10 ⁰ Gold	Material	B: Tape & Reel + CAP
	G2=30 ⁰ Gold	A: PBT	C: Tube
	G3=60 ⁰ Gold	B: P661	D: Tube+CAP
	G4=100 ⁰ Gold	C: P661	E: Tray
	G5=150 ⁰ Gold	D: LCP	F: Tape & Reel
	F0=30 ⁰ Gold		
	F0=Gold Flash		
	F1=10 ⁰ Gold/Tin		
	F2=30 ⁰ Gold/Tin		
	F3=60 ⁰ Gold/Tin		
	F6=100 ⁰ Gold/Tin		
	F7=150 ⁰ Gold/Tin		
	F9=300 ⁰ Gold/Tin		
	Silver Tin		
	Solderable Tin		

Dimension antitheses lis	
ITEM	A B
Standard	3.0 6.0
Alternate	

[illegible]