

HSF RoHS

1. 材料(MATERIAL)

成心: PA6T+30%G.F UL94V-0, 颜色: 黑色;
Housing: PA6T+30%G.F UL94V-0, Color: Black

Contact : Brass

额定电压 (Circuit Voltage): 3 AMP

接觸阻抗: 20 mΩ

绝缘阻抗: 1000 MΩ min

耐电压: AC 500V

温度范围: -40°C to $+105^{\circ}\text{C}$

Temperature Range: -40°C to +105°C

Ordering Information

3PXXM-22 XX X XXX X 2^{AN}

Plastics	No. of Pins Per Row	Contact	Plating	Insulator Material	Length Of Terminal	Packing
Height		Gold Flash				A: Tape Bag
10: ± 1.0	240P	G=10' Gold		B: PBT		B: Tape & Reel+CAP
15: ± 1.5		G=30' Gold		C: PBT		C: Tube
17: ± 1.7		G=50' Gold		D: LCP		D: Tube+CAP
20: ± 2.0		G=100' Gold				E: Tray
25: ± 2.54		G=150' Gold				F: Tape & Reel
		G=300' Gold				
		P0=Gold Flash				
		F1=1U' Gold/Tin				
		F2=3U' Gold/Tin				
		F3=5U' Gold/Tin				
		F6=10U' Gold/Tin				
		F7=15U' Gold/Tin				
		F9=30U' Gold/Tin				
		S0=fin				
		S1=Matte Tin				

Dimension antitheses list							
ITEM	B		H			D	C
Standard	6.0	1.0	1.5	1.7	2.0	2.54	0
Alternate							

[illegible]