



Specifications

备注(Remark)

1. 材料(MATERIAL)

胶芯: PA6T/LCP+30%G.F UL94V-0, 颜色: 黑色.

Housing: PA6T/LCP+30%G.F UL94V-0, Color: Black

四方针: 黄铜

Contact : Phosphor bronze

2. 特性 (Characteristics):

额定电流: 0.75 AMP

额定电压: 0.75 AMP.

接触电阻: 20 mΩ MAX.

接触电阻: 20 mΩ MAX.

绝缘电阻: 1000 MΩ min.

绝缘电阻: 1000 MΩ min.

耐压: AC 500V.

耐压: AC 500V.

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

Ordering Information

5PXXM- 22 XX XX X XXX X 1 Δ

Plastics	No. of Pins	Contact Plating	Insulator Material	Length	Packing
10:IE=1.0	2 30P	G=10" Gold	M:PA6T	0"	A:PE Bag
15:IE=1.5		G=30" Gold	R:PA6T	Terminal	B: Tape & Reel+CAP
		G=50" Gold	C:PA9T		C: Tube
		G=100" Gold	D:LCP		D: Tray
		G=150" Gold			E: Tray
		G=300" Gold			F: Tape & Reel
		P=10" Gold/Tin			
		P=30" Gold/Tin			
		P=50" Gold/Tin			
		P=100" Gold/Tin			
		P=150" Gold/Tin			
		P=300" Gold/Tin			
		Sn= Tin			
		Sn= Matte Tin			

1.00

2.40

6.00

Recommended P.C.B layout

1.00

B±0.25

Users can customize
此高度可定制

D±0.25

C±0.25

5.00±0.25

1.00XNo.of Contacts/2-1.00±0.2

1.00XNo.of Positions±0.25

Dimension antitheses list

ITEM	B	D	H	W	C
Standard	1.8	0.1	1.0	1.5	2.3 3.2
Alternate					

LIRCON 连润电子有限公司
Lrcon Electronics Co.,Ltd

PART NO.	5PXXM-22XXXXXXX1
TITLE:	1.0双排针 双塑 SMT
Customer No.	

SCALE	UNIT	Fit
A4	MM	DESIGN
1/1	CHECK	APPROVE

OPERATION	DRAW	LI	ANR	20/06/09
X.X ±0.40	DESIGN	张涛		
X.XX ±0.25	CHECK	罗荣军		
X.XXX ±0.15	APPROVE	方里军		
Angle ±3°	TOL			

CHANGE	APPROVE	DIM	APPROVE	APPROVE
—	—	—	—	—
—	—	—	—	—

REV	DATE	MODIFICATION DESCRIPTION
A1	20/06/09	Improve numbering instructions (完善编号标注说明)
A0	12/05/18	NEW