

温度范围: -40°C to $+105^{\circ}\text{C}$
Temperature Range: -40°C to $+105^{\circ}\text{C}$

A1	20/06/09	Improve numbering instructions (完善编号标注说明)		张涛	X.XX ±0.25	CHECK	罗荣军	SIZE A4	DESIGN	PART NO.	3F71M-21XXXXUX1
A0	12/05/18	NEW	——	——	X.XXX ±0.15	Angle ±3°	PROJ.	SHEET 1/1	CHECK	TITLE:	2.54S双排母 塑高7.1 U型 SMT6.5 PC脚0.65
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	DIM	TOL	APPROVE	方里军	APPROVE	Customer No.	

					OPERATION	DRAW	LIANR	20/06/09	SCALE	Fit	LARCON 连润电子有限公司 Lrcon Electronics Co.,Ltd	
					X.X	DESIGN	张涛		UNIT	MM		
A1	20/06/09	Improve numbering instructions (完善编号标注说明)	张涛		X.XX	CHECK	罗荣军		SIZE	DESIGN		
A0	12/05/18	NEW			X.XXX				SHEET	CHECK	TITLE:	3F71M-21XXXXXUX1
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	DIM	TOL	APPROVE	方里军	PROJ.	APPROVE	Customer No.	2.54S双排母 塑高7.1 U型 SMT6.5 PC脚0.65