



Specifications

备注(Remark)

1. 材料(MATERIAL)

胶芯: PA6T/LCP+30%G.F UL94V-0, 颜色: 黑色.

Housing: PA6T/LCP+30%G.F UL94V-0, Color: Black

四方针: 黄铜

Contact: Brass

2. 特性 (Characteristics):

额定电流: 2 AMP

额定电流: 2 AMP.

接触电阻: 20 mΩ MAX.

Contact Resistance: 20 mΩ MAX.

绝缘电阻: 1000 MΩ min.

Insulating Resistance: 1000 MΩ min.

耐电压: AC 500V.

Withstanding Voltage: AC 500V.

温度范围: -40°C to +105°C

Temperature Range: -40°C to +105°C

Ordering Information

2B64M- 2 XX XX X X X 1 Δ

No. of Pins	Contact Plating	Insulator Color	Packing
6 68P	Gold Flash	Material B: Black	A: PE Bag
	G=10" Gold	B: PA6T	B: Tape & Reel+CAP
	G=30" Gold	C: PA9T	C: Tube
	G=50" Gold	D: LCP	D: Tube+CAP
	G=100" Gold		E: Tray
	G=150" Gold		F: Tape & Reel
	G=200" Gold		
	P=Gold Flash		
	F=10" Gold/Tin		
	F=30" Gold/Tin		
	F=50" Gold/Tin		
	F=100" Gold/Tin		
	F=150" Gold/Tin		
	F=200" Gold/Tin		
	Sn=Sn		
	Sn=Matte Tin		

Recommended P.C.B layout

Users can customize
此高度可定制

LRCON 连润电子有限公司
Lrcon Electronics Co., Ltd

PART NO. 2B64M-2XXXXXX1
TITLE: 2.0莫仕筒牛 塑高6.4 SMT 加塑胶 带窗口
Customer No.

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	DIM	ANGLE	TOL	APPROVE	方里军	罗荣军	张涛	DESIGN	UNIT	SCALE	Fit
A1	20/06/09	Improve numbering instructions (完善编号标注说明)	Δ	张涛	X.X	±0.40		DESIGN	张涛						MM
A0	12/05/18	NEW			X.XX	±0.25		CHECK	罗荣军				A4		DESIGN
					X.XXX	±0.15		CHECK					SHEET	1/1	CHECK
					Angle	±3°		APPROVE					PROJ.		APPROVE