



Specifications

备注(Remark)

1. 材料(MATERIAL)

胶芯: PA6T+30%G.F UL94V-0, 颜色: 黑色

Housing: PA6T+30%G.F UL94V-0, Color: Black

四方针: 黄铜

Contact: Brass

2. 特性 (Characteristics):

额定电流: 1 AMP

额定电压: 1000 V

接触电阻: 20 mΩ MAX.

接触电阻: 20 mΩ MAX.

绝缘电阻: 1000 MΩ min.

绝缘电阻: 1000 MΩ min.

耐电压: AC 500V.

耐电压: AC 500V.

温度范围: -40°C to +105°C

温度范围: -40°C to +105°C

Ordering Information

4B96R- 1 XX XX X X X 1 Δ

No. of Pins	Contact Plating	Insulator	Color	Packing
6 68R	Gold Flash	Material	B: Black	C: Tube
	G1=10" Gold	B: PA6T		E: Tray
	G4=50" Gold	C: PA6T		F: Tape
	G5=50" Gold	D: LCP		
	G6=100" Gold			
	G7=150" Gold			
	G8=500" Gold			
	P0=Gold Flash			
	F1=10" Gold/Tin			
	F4=30" Gold/Tin			
	F6=50" Gold/Tin			
	F8=100" Gold/Tin			
	F7=150" Gold/Tin			
	F9=300" Gold/Tin			
	SN=Fin			
	SM=Matte Tin			

LRCON 连润电子有限公司
Lrcon Electronics Co., Ltd

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	DIM	TOL	APPROVE	方里军	罗荣军	张涛	DESIGN	UNIT	SCALE	Fit	MM	4B96R-1XXXXXX1	PART NO.	TITLE:	Customer No.
A1	20/06/09	Improve numbering instructions (完善编号标注说明)	Δ	张涛	X.X	±0.40	张涛	张涛	张涛	张涛	张涛	A4	DESIGN	DESIGN	MM	4B96R-1XXXXXX1	4B96R-1XXXXXX1	1.27*2.54筒牛 塑高9.65 90度	
A0	12/05/18	NEW	—	—	X.XX	±0.25	—	—	—	—	—	1/1	CHECK	CHECK					
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	DIM	TOL	APPROVE	方里军	罗荣军	张涛	DESIGN	UNIT	SCALE	Fit	MM	4B96R-1XXXXXX1	PART NO.	TITLE:	Customer No.