

Specifications

备注(Remark)

1. 材料(MATERIAL)

胶芯: LCP/PA6T+30%G.F UL94V-0, 颜色: 黑色。

Housing: LCP/PA6T+30%G.F UL94V-0, Color: Black

四方针：黄铜

Contact: Brass

2. 特性 (characteristics):

额定电流: 1 AMP

Rating Current: 1 AMP.

接触阻抗: 20 mΩ MAX.

接触电阻: 20 mΩ MAX.
Contact Resistance: 20 mΩ MAX.

绝缘阻抗: 1000 MΩ min.

Insulating Resistance: 1000 M Ω min.

耐电压: AC 500V.

耐电压: AC 500V.
Withstanding Voltage: AC 500V.

温度范围: -40°C to $+105^{\circ}\text{C}$

温度范围: -40°C to +105°C
Temperature Range: -40°C

temperature range: 40 °C to 100 °C

Ordering Information

1E02M-1 XXX XX X X X 1

No. of Pins	Contact	Plating	Insulator	Color	Packing
6~68P	G0-Gold	Flash	Material:	B:Black	A:PE Bag

G1=1u"Gold
C4=3u"Gold
B: Tape & Reel+CAP
B: PA6T
C: PA9T
E: Tray

G4=3D Gold
G5=5u"Gold
C:PA91
D:LCP
E:IR91

G6=10u"Gold

67=15u"Gold
69=30u"Gold

FO-Gold Flash

FI=IU"Gold/Tin
E4=20"C-14/T:2

14=30"Gold/Tin
15=50"Gold/Tin

F6=10U"Gold/Tin

F7=15U"Gold/Tin
F8=20U"C-14/Ti=

$\text{Fg} \equiv 300^\circ \text{Gold/Tin}$
 $\text{SN} \equiv \text{Tin}$

[illegible]